
LURALINE LIGHTING

Project: _____ Fixture Type: _____





RLM CS20 CORDX H: 14 W: 20.25 OAL: 50.75

Description

20" RLM pendant with 36" Black 18-3 cord. (White cord supplied with white fixtures)

Specifications

Housing	Spun aluminum shade with stamped steel canopy*
Diffuser/Optics	TurboLED omni-directional silicone optic
Light Source	LED
Max Watts	26.98
Electrical	TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
Mounting	Mounts over 4" recessed outlet box.
Certification	Manufactured in accordance with U.L. standard 1598 - For dry locations only

Ordering Guide: Choose from each category, using designated code to specify.

CS20 CORDX				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

LOZ - Omni-directional Optic

Light Source

TL11 HO - 10.99W/40K 2470 Lm, 120V dimmable
TL11 - 11.3W/30K 2075 Lm, 120V dimmable
TL13 HO - 12.62W/40K 2756 Lm, 120V dimmable
TL13 - 12.99W/30K 2352 Lm, 120V dimmable
TL14 HO - 14.28W/40K 3040 Lm, 120V dimmable
TL15 - 14.69W/30K 2626 Lm, 120V dimmable
TL16 HO - 15.94W/40K 3320 Lm, 120V dimmable
TL16 - 16.41W/30K 2895 Lm, 120V dimmable
TL26 HO - 26.16W/40K 4938 Lm, 0-10V dimmable
TL27 - 26.98W/30K 4428 Lm, 0-10V dimmable

Finish

Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from Luraline Pallette
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
* Subject to Surcharge

Extras (Order Separately)

27K Non-Stock item - consult factory for availability
35K Neutral White
DIM010 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
DWG20 20" Drop Wire Guard
SSP 10KV 120-277V Supplemental Surge Protection

Specifications subject to change without notice.
800-940-6588
Sales@luraline.com
www.luraline.com

Lighting Your Way